

SECTION 1: IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY/UNDERTAKING

1.1 Trade name	CARBONFINISH Compound Black
Article number	PBLKSFI
1.2 Identified uses	Polishing compound
Product category	product for surface finishing
1.3 Supplier	BAXT Products is a trading name of AMBA Group Ltd Unit 3 Castlehill Business Park, Flexford Road North Baddesley, Southampton, SO52 9DF, United Kingdom Tel: 023 8025 1100 Email: sales@baxt-products.com Web: https://baxt-products.com/
1.4 Emergency telephone	UK: NPIS National Poisons Information Centre Tel: +44 0344 892 0111

SECTION 2: HAZARDS IDENTIFICATION

2.1 Classification



GHS07
exclamation mark

Eye Irrit. 2 H319

Signal word

WARNING

Hazard statements

H319 Causes serious eye irritation.

Precautionary statements

P102 Keep out of reach of children.

P101 If medical advice is needed, have product container or label at hand.

P305+P351+P338 EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

P280 Wear eye protection / face protection.

P337+P313 If eye irritation persists: Get medical advice / attention.

P264 Wash hands thoroughly after handling.

Additional information

EUH066 Repeated exposure may cause skin dryness or cracking.

EUH208 Contains: 1,2-Benzisothiazol-3(2H)-one May produce an allergic reaction.





2.3 Other hazards

PBT: On the basis of available data, the product does not contain any PBT or vPvB in percentage \geq than 0.1%.

vPvB: On the basis of available data, the product does not contain any PBT or vPvB in percentage \geq than 0.1%.

The product does not contain substances with endocrine disrupting properties in concentration \geq 0.1%.

SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS

SUBSTANCE	IDENTIFIERS	GHS	CLASSIFICATIONS	CONCENTRATION
Hydrocarbons, C11-C14, n-alkanes, isoalkanes, cyclics, <2% aromatics	EC: 926-141-6 CAS: 64742-47-8 Reg.nr.: 01-2119456620-43	 	Asp. Tox. 1 H304 EUH066 EUH066	15 ≤ x < 16,5
Hydrocarbons, C12-C15, n-alkanes, isoalkanes, cyclic, <2% aromatics	EC: 920-107-4 CAS: 64742-47-8 Reg.nr.: 01-2119453414-43	 	Asp. Tox. 1 H304 EUH066 EUH066	7 ≤ x < 8
Hydrocarbons C10-13 n-iso cyclic alkanes <2% aromatic	EC: 918-481-9 CAS: 64742-48-9 Reg.nr.: 01-2119457273-39	 	Asp. Tox. 1 H304	4,5 ≤ x < 5
Vaseline oil	EC: 232-455-8 CAS: 8042-47-5 Reg.nr.: 01-2119487078-27-xxxx	 	Asp. Tox. 1 H304	3,5 ≤ x < 4
Alcohols, C12-14, ethoxylated	EC: 500-213-3 CAS: 68439-50-9	   	Acute Tox. 4 H302 Eye Dam. 1 H318 Aquatic Chronic 3 H412	2,5 ≤ x < 3
2-(2-BUTOXYETHOXY)ETHANOL	EC: 203-961-6 CAS: 112-34-5 Reg.nr.: 01-2119475104-44-xxxx		Eye Irrit. 2 H319	0,5 ≤ x < 0,6
1,2- Benzisothiazol-3(2H)-one	EC: 220-120-9 CAS: 2634-33-5 Reg.nr.: 01-2120761540-60-xxxx	   	Acute Tox. 4 H302 Eye Dam. 1 H318 Skin Irrit. 2 H315 Skin Sens. 1 H317 Aquatic Acute 1 M=1 H400	0 ≤ x < 0,05

SECTION 4: FIRST AID MEASURES

4.1 After inhalation

INHALATION: Remove to open air. If the subject stops breathing, administer artificial respiration. Get medical advice/attention immediately.

After skin contact

SKIN: Remove contaminated clothing. Rinse skin with a shower immediately. Wash contaminated clothing before using it again.

After eye contact

EYES: Remove contact lenses, if present. Wash immediately with plenty of water for at least 15 minutes, opening the eyelids fully. If problem persists, seek medical advice.

After ingestion

INGESTION: Get medical advice/attention immediately. Do not induce vomiting. Do not administer anything not explicitly authorised by a doctor.

4.2 Most important symptoms and effects

Specific information on symptoms and effects caused by the product are unknown.

4.3 Indication of immediate medical attention

Information not available

SECTION 5: FIREFIGHTING MEASURES

5.1 Suitable extinguishing media

SUITABLE EXTINGUISHING EQUIPMENT The extinguishing equipment should be of the conventional kind: carbon dioxide, foam, powder and water spray.

Unsuitable extinguishing media

UNSUITABLE EXTINGUISHING EQUIPMENT None in particular.

5.2 Special hazards

HAZARDS CAUSED BY EXPOSURE IN THE EVENT OF FIRE Do not breathe combustion products.

5.3 Advice for firefighters

GENERAL INFORMATION Use jets of water to cool the containers to prevent product decomposition and the development of substances potentially hazardous for health. Always wear full fire prevention gear. Collect extinguishing water to prevent it from draining into the sewer system. Dispose of contaminated water used for extinction and the remains of the fire according to applicable regulations.

Protective equipment

SPECIAL PROTECTIVE EQUIPMENT FOR FIRE-FIGHTERS Normal fire fighting clothing i.e. fire kit (BS EN 469), gloves (BS EN 659) and boots (HO specification A29 and A30) in combination with self-contained open circuit positive pressure compressed air breathing apparatus (BS EN 137).

SECTION 6: ACCIDENTAL RELEASE MEASURES

6.1 Personal precautions, protective equipment and emergency procedures

Block the leakage if there is no hazard. Wear suitable protective equipment (including personal protective equipment referred to under Section 8 of the safety data sheet) to prevent any contamination of skin, eyes and personal clothing. These indications apply for both processing staff and those involved in emergency procedures.

6.2 Environmental precautions

The product must not penetrate into the sewer system or come into contact with surface water or ground water.

6.3 Methods and material for containment and cleaning up

Collect the leaked product into a suitable container. Evaluate the compatibility of the container to be used, by checking section 10. Absorb the remainder with inert absorbent material. Make sure the leakage site is well aired. Contaminated material should be disposed of in compliance with the provisions set forth in point 13.

6.4 Reference to other sections

Any information on personal protection and disposal is given in sections 8 and 13.

SECTION 7: HANDLING AND STORAGE**7.1 Precautions for safe handling**

Before handling the product, consult all the other sections of this material safety data sheet. Avoid leakage of the product into the environment. Do not eat, drink or smoke during use. Remove any contaminated clothes and personal protective equipment before entering places in which people eat.

7.2 Conditions for safe storage

Store only in the original container. Store the containers sealed, in a well ventilated place, away from direct sunlight. Keep containers away from any incompatible materials, see section 10 for details.

7.3 Specific end use(s)

Information not available

SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

8.1 Control parameters

CAS	SUBSTANCE	LIMITS
	Hydrocarbons, C11-C14, n-alkanes, isoalkanes, cyclics, <2% aromatics	Health - Derived no-effect level - DNEL / DMEL: Effects on consumers - Oral: Acute systemic NPI, Chronic systemic NPI; Inhalation: Acute local NEA, Acute systemic NPI, Chronic local NPI, Chronic systemic NPI; Skin: Acute local NPI, Acute systemic NPI, Chronic local LOW, Chronic systemic NPI. Effects on workers - Inhalation: Acute local NPI, Acute systemic NPI, Chronic local NPI, Chronic systemic NPI; Skin: Acute local NPI, Acute systemic NPI, Chronic local LOW, Chronic systemic NPI.
64742-47-8	Hydrocarbons, C12-C15, n-alkanes, isoalkanes, cyclic, <2% aromatics	OEL EU TWA/8h: 200 mg/m3 SKIN non aerosol
64742-48-9	Hydrocarbons C10-13 n-iso cyclic alkanes <2% aromatic	OEL EU TWA/8h: 1200 mg/m3, 184 ppm
8042-47-5	Vaseline oil	TLV-ACGIH TWA/8h: 5 mg/m3, STEL/15min: 10 mg/m3 nebbie d'olio
112-34-5	2-(2-BUTOXYETHOXY)ETHANOL	MAK DEU TWA/8h: 67 mg/m3, 10 ppm; STEL/15min: 100,5 mg/m3, 15 ppm VLA ESP TWA/8h: 67,5 mg/m3, 10 ppm; STEL/15min: 101,2 mg/m3, 15 ppm TLV GRC TWA/8h: 67,5 mg/m3, 10 ppm; STEL/15min: 101,2 mg/m3, 15 ppm VLEP ITA TWA/8h: 67,5 mg/m3, 10 ppm; STEL/15min: 101,2 mg/m3, 15 ppm RD LTU TWA/8h: 100 mg/m3, 15 ppm; STEL/15min: 200 mg/m3, 30 ppm TGG NLD TWA/8h: 50 mg/m3; STEL/15min: 100 mg/m3 SKIN VLE PRT TWA/8h: 67,5 mg/m3, 10 ppm; STEL/15min: 101,2 mg/m3, 15 ppm NDS/NDSch POL TWA/8h: 67 mg/m3; STEL/15min: 100 mg/m3 TLV ROU TWA/8h: 150 mg/m3; STEL/15min: 250 mg/m3 MV SVN TWA/8h: 67,5 mg/m3, 10 ppm; STEL/15min: 101,25 mg/m3, 15 ppm OEL EU TWA/8h: 67,5 mg/m3, 10 ppm; STEL/15min: 101,2 mg/m3, 15 ppm TLV-ACGIH TWA/8h: 66 mg/m3, 10 ppm

Engineering controls

As the use of adequate technical equipment must always take priority over personal protective equipment, make sure that the workplace is well aired through effective local aspiration. When choosing personal protective equipment, ask your chemical substance supplier for advice. Personal protective equipment must be CE marked, showing that it complies with applicable standards. Provide an emergency shower with face and eye wash station. ENVIRONMENTAL EXPOSURE CONTROLS The emissions generated by manufacturing processes, including those generated by ventilation equipment, should be checked to ensure compliance with environmental standards.

Respiratory protection

RESPIRATORY PROTECTION Respiratory protection devices must be used if the technical measures adopted are not suitable for restricting the worker's exposure to the threshold values considered. Use a mask with a type A filter whose class (1, 2 or 3) must be chosen according to the limit of use concentration. (see standard EN 14387). If the substance considered is odourless or its olfactory threshold is higher than the corresponding TLV-TWA and in the case of an emergency, wear open-circuit compressed air breathing apparatus (in compliance with standard EN 137) or external air-intake breathing apparatus (in compliance with standard EN 138). For a correct choice of respiratory protection device, see standard EN 529.

Hand protection

HAND PROTECTION Protect hands with category III work gloves. The following should be considered when choosing work glove material (see standard EN 374): compatibility, degradation, permeability time. The work gloves' resistance to chemical agents should be checked before use, as it can be unpredictable. The gloves' wear time depends on the duration and type of use.

Eye protection

EYE PROTECTION Wear airtight protective goggles (see standard EN ISO 16321).

Skin protection

SKIN PROTECTION Wear category I professional long-sleeved overalls and safety footwear (see Regulation 2016/425 and standard EN ISO 20344). Wash body with soap and water after removing protective clothing.

SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

Form	viscous liquid
Colour	black
Odour	characteristic
pH	6
Melting / freezing point	not available
Boiling point and range	not available
Flash point	> 60 °C
Flammability	not available
Ignition temperature	not available
Decomposition temperature	not available
Explosion limits lower	not available
Explosion limits upper	not available
Vapour pressure	not available
Relative density	1,1
Vapour density	not available
Solubility in water	not available
Partition coefficient	not available
Viscosity	not available
Other information	Particle characteristics: not applicable 9.2.1. Information with regard to physical hazard classes Information not available 9.2.2. Other safety characteristics Information not available

SECTION 10: STABILITY AND REACTIVITY

10.1 Reactivity

There are no particular risks of reaction with other substances in normal conditions of use.

10.2 Chemical stability

The product is stable in normal conditions of use and storage.

10.3 Possibility of hazardous reactions

No hazardous reactions are foreseeable in normal conditions of use and storage. 2-(2-BUTOXYETHOXY)ETHANOL May react with: oxidising substances. May form peroxides with: oxygen. Develops hydrogen on contact with: aluminium. May form explosive mixtures with: air.

10.4 Conditions to avoid

None in particular. However the usual precautions used for chemical products should be respected. 2-(2-BUTOXYETHOXY)ETHANOL Avoid exposure to: air.

10.5 Incompatible materials

2-(2-BUTOXYETHOXY)ETHANOL Incompatible with: oxidising substances, strong acids, alkaline metals.

10.6 Hazardous decomposition products

2-(2-BUTOXYETHOXY)ETHANOL May develop: hydrogen.

SECTION 11: TOXICOLOGICAL INFORMATION

11.1 Acute toxicity

In the absence of experimental data for the product itself, health hazards are evaluated according to the properties of the substances it contains, using the criteria specified in the applicable regulation for classification. It is therefore necessary to take into account the concentration of the individual hazardous substances indicated in section 3, to evaluate the toxicological effects of exposure to the product. ATE (Inhalation) of the mixture: Not classified (no significant component) ATE (Oral) of the mixture: >2000 mg/kg ATE (Dermal) of the mixture: Not classified (no significant component) 2-(2-BUTOXYETHOXY)ETHANOL WORKERS: inhalation; contact with the skin. It can be absorbed by inhalation, ingestion and skin contact; it is irritating to the skin and especially to the eyes. Spleen damage may occur. At room temperature the danger of inhalation is unlikely, due to the low vapor pressure of the substance.

LD/LC50 values relevant for classification

CAS	SUBSTANCE	VALUES
	ALUMINIUM OXYDE	LD50 (Oral): > 2000 mg/kg ratto LC50 (Inhalation mists/powders): > 2,3 mg/l/4h ratto
64742-47-8	Hydrocarbons, C11-C14, n-alkanes, isoalkanes, cyclics, <2% aromatics	LD50 (Dermal): > 5000 mg/kg Coniglio LD50 (Oral): > 5000 mg/kg Ratto
64742-47-8	Hydrocarbons, C12-C15, n-alkanes, isoalkanes, cyclic, <2% aromatics	LD50 (Dermal): > 5000 mg/kg Coniglio LD50 (Oral): > 5000 mg/kg Ratto LC50 (Inhalation vapours): > 6100 mg/m3 Ratto
64742-48-9	Hydrocarbons C10-I3 n-iso cyclic alkanes <2% aromatic	LD50 (Dermal): > 2000 mg/kg ratto LD50 (Oral): > 5000 mg/kg ratto
8042-47-5	Vaseline oil	LD50 (Dermal): > 2000 mg/kg LD50 (Oral): > 5000 mg/kg LC50 (Inhalation vapours): > 5000 mg/l/1h
68439-50-9	Alcohols, C12-14, ethoxylated	LD50 (Oral): > 300 mg/kg ratto
112-34-5	2-(2-BUTOXYETHOXY)ETHANOL	LD50 (Dermal): 2764 mg/kg Rabbit LD50 (Oral): 3384 mg/kg Rat
2634-33-5	1,2- Benzisothiazol-3(2H)-one	LD50 (Oral): 1400 mg/kg Rat

Primary irritant effects, skin corrosion/irritation

SKIN CORROSION / IRRITATION Repeated exposure may cause skin dryness or cracking.

Serious eye damage/irritation

SERIOUS EYE DAMAGE / IRRITATION Causes serious eye irritation

Respiratory or skin sensitisation

RESPIRATORY OR SKIN SENSITISATION May produce an allergic reaction. Contains: 1,2- Benzisothiazol-3(2H)-one

Germ cell mutagenicity

GERM CELL MUTAGENICITY Does not meet the classification criteria for this hazard class

Carcinogenicity

CARCINOGENICITY Does not meet the classification criteria for this hazard class

Reproductive toxicity

REPRODUCTIVE TOXICITY Does not meet the classification criteria for this hazard class

STOT - single exposure

STOT - SINGLE EXPOSURE Does not meet the classification criteria for this hazard class

STOT - repeated exposure

STOT - REPEATED EXPOSURE Does not meet the classification criteria for this hazard class

Aspiration hazard

ASPIRATION HAZARD Does not meet the classification criteria for this hazard class

SECTION 12: ECOLOGICAL INFORMATION

12.1 Aquatic toxicity

CAS	SUBSTANCE	VALUES
68439-50-9	Alcohols, C12-14, ethoxylated	Chronic NOEC for Fish > 0.1 mg/l Chronic NOEC for Crustacea > 0.1 mg/l Chronic NOEC for Algae / Aquatic Plants > 0.1 mg/l
	ISOPROPYL MYRISTATE	EC50 - for Crustacea < 100 mg/l/48h Chronic NOEC for Crustacea > 100 mg/l
112-34-5	2-(2-BUTOXYETHOXY)ETHANOL	LC50 - for Fish 1300 mg/l/96h EC50 - for Crustacea > 100 mg/l/48h
	ALUMINIUM OXYDE	EC50 - for Crustacea > 100 mg/l/48h Daphnia magna EC50 - for Algae / Aquatic Plants > 100 mg/l/72h Selenastrum capricornutum
64742-47-8	Hydrocarbons, C12-C15, n-alkanes, isoalkanes, cyclic, <2% aromatics	LC50 - for Fish > 1000 mg/l/96h Oncorhynchus mykiss EC50 - for Crustacea > 1000 mg/l/48h Daphnia magna EC50 - for Algae / Aquatic Plants > 1000 mg/l/72h Pseudokirchneriella subcapitata
2634-33-5	1,2- Benzisothiazol-3(2H)-one	LC50 - for Fish 10 mg/l/96h Fish EC50 - for Crustacea 4.4 mg/l/48h Daphnia magna EC50 - for Algae / Aquatic Plants 0.037 mg/l/72h
64742-47-8	Hydrocarbons, C11-C14, n-alkanes, isoalkanes, cyclics, <2% aromatics	LC50 - for Fish 1000 mg/l/96h

12.2 Persistence and degradability

Alcohols, C12-14, ethoxylated: Rapidly degradable ISOPROPYL MYRISTATE: Rapidly degradable 2-(2-BUTOXYETHOXY)ETHANOL: Solubility in water 1000 - 10000 mg/l; Rapidly degradable ALUMINIUM OXYDE: NOT rapidly degradable Vaseline oil: NOT rapidly degradable Hydrocarbons, C12-C15, n-alkanes, isoalkanes, cyclic, <2% aromatics: Inherently degradable Hydrocarbons, C11-C14, n-alkanes, isoalkanes, cyclics, <2% aromatics: Rapidly degradable Hydrocarbons C10-13 n-iso cyclic alkanes <2% aromatic: Inherently degradable

12.3 Bioaccumulative potential

2-(2-BUTOXYETHOXY)ETHANOL Partition coefficient: n-octanol/water 1

12.4 Mobility in soil

Information not available

12.5 PBT and vPvB assessment

On the basis of available data, the product does not contain any PBT or vPvB in percentage \geq than 0.1%.

12.6 Other adverse effects

12.6. Endocrine disrupting properties Based on the available data, the product does not contain substances listed in the main European lists of potential or suspected endocrine disruptors with environmental effects under evaluation. 12.7. Other adverse effects Information not available

General notes

Use this product according to good working practices. Avoid littering. Inform the competent authorities, should the product reach waterways or contaminate soil or vegetation.

SECTION 13: DISPOSAL CONSIDERATIONS

13.1 Waste treatment methods

Reuse, when possible. Product residues should be considered special hazardous waste. The hazard level of waste containing this product should be evaluated according to applicable regulations. Disposal must be performed through an authorised waste management firm, in compliance with national and local regulations.

Uncleaned packaging

CONTAMINATED PACKAGING Contaminated packaging must be recovered or disposed of in compliance with national waste management regulations.

SECTION 14: TRANSPORT INFORMATION

14.2 - 14.4 Transport details by mode

MODE	SHIPPING NAME	CLASS	LABEL	PACKING GROUP	LIMITED QTY
ADR	not applicable	not applicable	not applicable	not applicable	
IMDG	not applicable	not applicable	not applicable	not applicable	
IATA	not applicable	not applicable	not applicable	not applicable	

14.5 Environmental hazards

not applicable

14.6 Special precautions for user

not applicable

14.7 MARPOL II / IBC Code bulk transport

Information not relevant

SECTION 15: REGULATORY INFORMATION

15.1 Safety, health and environmental regulations

Restrictions relating to the product or contained substances pursuant to Annex XVII to EC Regulation 1907/2006 Product Point 3 Contained substance Point 75 Regulation (EU) 2019/1148 - on the marketing and use of explosives precursors not applicable Substances subject to authorisation (Annex XIV REACH) None Substances subject to exportation reporting pursuant to Regulation (EU) 649/2012: None Substances subject to the Rotterdam Convention: None Substances subject to the Stockholm Convention: None Healthcare controls Workers exposed to this chemical agent must not undergo health checks, provided that available risk-assessment data prove that the risks related to the workers' health and safety are modest and that the 98/24/EC directive is respected.

Directive 2012/18/EU

Seveso category None

REACH Annex XVII

Product: Point 3 Contained substance: Point 75

SVHC (Article 57)

On the basis of available data, the product does not contain any SVHC in percentage \geq than 0.1%.

15.2 Chemical safety assessment

A chemical safety assessment has not been performed for the preparation/for the substances indicated in section 3.

SECTION 16: OTHER INFORMATION

Issued by	BAXT Products, Technical
Date issued	22/06/2026
Source revision date	17/04/2026
Source version	14

Note for users: The information contained in the present sheet are based on our own knowledge on the date of the last version. Users must verify the suitability and thoroughness of provided information according to each specific use of the product. This document must not be regarded as a guarantee on any specific product property. The use of this product is not subject to our direct control; therefore, users must, under their own responsibility, comply with the current health and safety laws and regulations. The producer is relieved from any liability arising from improper uses. Provide appointed staff with adequate training on how to use chemical products. CALCULATION METHODS FOR CLASSIFICATION Chemical and physical hazards: Product classification derives from criteria established by the CLP Regulation, Annex I, Part 2. The data for evaluation of chemical-physical properties are reported in section 9. Health hazards: Product classification is based on calculation methods as per Annex I of CLP, Part 3, unless determined otherwise in Section 11. Environmental hazards: Product classification is based on calculation methods as per Annex I of CLP, Part 4, unless determined otherwise in Section 12.

Relevant H-phrases

Acute Tox. 4	Acute toxicity, category 4	Aquatic Chronic 3	Hazardous to the aquatic environment, chronic toxicity, category 3
Asp. Tox. 1	Aspiration hazard, category 1	H302	Harmful if swallowed.
Eye Dam. 1	Serious eye damage, category 1	H304	May be fatal if swallowed and enters airways.
Eye Irrit. 2	Eye irritation, category 2	H318	Causes serious eye damage.
Skin Irrit. 2	Skin irritation, category 2	H319	Causes serious eye irritation.
Skin Sens. 1	Skin sensitization, category 1	H315	Causes skin irritation.
Aquatic Acute 1	Hazardous to the aquatic environment, acute toxicity, category 1	H317	May cause an allergic skin reaction.
		H400	Very toxic to aquatic life.
		H412	Harmful to aquatic life with long lasting effects.
		EUH066	Repeated exposure may cause skin dryness or cracking.

Abbreviations and acronyms

ADR	European Agreement concerning the carriage of Dangerous goods by Road	OEL	Occupational Exposure Level
ATE	Acute Toxicity Estimate	PBT	Persistent, bioaccumulative and toxic
CAS	Chemical Abstract Service Number	PEC	Predicted environmental Concentration
CE50	Effective concentration (required to induce a 50% effect)	PEL	Predicted exposure level
CE	Identifier in ESIS (European archive of existing substances)	PMT	Persistent, mobile and toxic
CLP	Regulation (EC) 1272/2008	PNEC	Predicted no effect concentration
DNEL	Derived No Effect Level	REACH	Regulation (EC) 1907/2006
EmS	Emergency Schedule	RID	Regulation concerning the international transport of dangerous goods by train
GHS	Globally Harmonized System of classification and labeling of chemicals	TLV	Threshold Limit Value
IATA DGR	International Air Transport Association Dangerous Goods Regulation	TLV CEILING	Concentration that should not be exceeded during any time of occupational exposure.
IC50	Immobilization Concentration 50%	TWA	Time-weighted average exposure limit
IMDG	International Maritime Code for dangerous goods	TWA STEL	Short-term exposure limit
IMO	International Maritime Organization	VOC	Volatile organic Compounds
INDEX	Identifier in Annex VI of CLP	vPvB	Very persistent and very bioaccumulative
LC50	Lethal Concentration 50%	vPvM	Very persistent and very mobile
LD50	Lethal dose 50%	WGK	Water hazard classes (German).

Changes to previous review: The following sections were modified: 03 / 08 / 11 / 12.